

Nu-Metrics Traffic Analyzer Study

Computer Generated Summary Report City: City of Fairfax

Street: Sager Ave. #2 Red

A study of vehicle traffic was conducted with HI-STAR unit number 1039. The study was done in the East Bound lane on Sager Ave. using counter #2 Red as shown on attached drawing. The counter was placed East of Walters Ct. The study began on 01/06/2004 at 12:00 PM and concluded on 01/09/2004 at 12:00 PM, lasting a total of 72 hours. Data was recorded in 60 minute time periods. The total recorded volume of traffic showed 5,406 vehicles passed through the location with a peak volume of 294 on 01/06/2004 at 05:00 PM and a minimum volume of 3 on 01/07/2004 at 03:00 AM. The AADT Count for this study was 1,802.

SPEED

Chart 1 lists the values of the speed bins and the total traffic volume for each bin.

Chart 1							
0 to 9	10 to 14	15 to 19	20 to 24	25 to 29	30 to 34	35 to 39	40 >
0	57	311	1685	2186	744	115	46

At least half of the vehicles were traveling in the 25 - 29 mph range or a lower speed. The average speed for all classified vehicles was 26 mph with 60.0 percent exceeding the posted speed of 25 mph. The HI-STAR found 3.13 percent of the total vehicles were traveling in excess of 35 mph. The mode speed for this traffic study was 25 mph and the 85th percentile was 30.90 mph.

CLASSIFICATION

Chart 2 lists the values of the eight classification bins and the total traffic volume accumulated for each bin.

Chart 2							
0 to 20	21 to 27	28 to 39	40 to 49	50 to 59	60 to 69	70 to 79	80 >
4954	146	39	3	1	1	0	0

Most of the vehicles classified during the study were Passenger Cars. The number of Passenger Cars in the study was 5,100 which represents 99.10 percent of the total classified vehicles. The Number of Small Trucks in the study was 39 which represents 0.80 percent of the total classified Vehicles. The number of Trucks/Buses in the study was 3 which represents 0.10 percent of the total classified vehicles. The number of Tractor Trailers in the study was 2 which represents 0.00 percent of the total classified vehicles.

HEADWAY

During the peak time period, on 01/06/2004 at 05:00 PM the average headway between the vehicles was 12.2 seconds. The slowest traffic period was on 01/07/2004 at 03:00 AM. During this slowest period, the average headway was 900.0 seconds.

WEATHER

The roadway surface temperature over the period of the study varied between 25 and 52 degrees Fahrenheit. The HI-STAR determined that the roadway surface was Dry 100.00 percent of the time.